

27 inches

# KDS/Embedded

Integrated machine



**Embedded / Wall mounted / Desktop**

# Selling point



## 10 Point touch

Accurate and sensitive capacitive screen



## Waterproof

Front panel waterproof and dustproof



## 24-hour operation

High and low temperature resistance, suitable for any environment



## Easy installation

Embedded / Wall mounted  
Desktop mounted



## Multiple interfaces

Rich interfaces to meet all your needs



## Silent without fan

Long lasting stability with zero noise



## Strong compatibility

Professional industrial control motherboard



## Metal body

Not prone to aging, fast heat dissipation



## Customized




Batch procurement, supporting customization

# Parameter




<b>Supply voltage</b>	100V-240V
<b>Host voltage</b>	12V 5A
<b>Display</b>	27"inch resolution 1920* 1080, 16:9 TFT LED
<b>Touch screen</b>	10point Capacitive Touch
<b>CPU</b>	Intel Baytrail J1900 / J4125 / J6412 /I3 / I5 (optional)
<b>Memory</b>	4GB / 8GB /16GB for optional
<b>Hard disk</b>	64G / 128G / 256G SSD / 500G HDD for optional
<b>COM</b>	2*RS232COM ports
<b>USB</b>	4-6 USB
<b>Interface</b>	RJ 45*1 / USB2.0*2 / USB3.0*4 / HDMI*1 / VGA*1 Audio*1 / Dc in*1
<b>Material quality</b>	Metal
<b>Install</b>	Embedded / Wall mounted / Desktop
<b>Work environment</b>	-10°C——60°C
<b>MSR</b>	/
<b>Total body weight</b>	7.45KG
<b>Packaging volume</b>	75*13.2*48CM

# Various Size



For more customized sizes, please consult customer service

Host size: 308mm in length, 30mm in width, and 200mm in height



Acoustic aperture

Heat dissipation hole

Host air outlet



DC in    HDMI    VGA    USB 3.0    RJ45    Audio



COM1    COM2



WiFi    USB 2.0

# KDS/Embedded




# KDS/Hanging type



# Fully compatible



Windows



Linux



Abdroid



**\*Install Windows by default**



# Industrial grade protection




Front panel pure flat support waterproof

## Easily handle various scenarios



Intelligent healthcare



CNC lathe



Self-service machine



Industrial control



Restaurant




Supermarket

# KDS/Wall mounted



## Installation method

1




The bracket hanging on the wall is installed on the wall surface

2



The bracket hanging part is installed on the back of the machine

3



Insert the bracket part into the wall hanging part

# High-quality



## Capacitive screen

10 finger stable touch, fast and convenient



## Pure plane

No dead corners, No blind spots



## LONG SERVICE LIFE

Wear resistant, low maintenance cost



Accurate touch control, responsive

# High and low temperature resistance



**-10°C — 60°C**

Resistant to high and low temperature operation



**High hardness**

Wear resistance and compression resistance



**0% — 90%**

Adapt to all difficult environments




**60°C**



**-10°C**

# Fanless cooling system



**Long exhaust and heat dissipation hole design reduces CPU operating pressure and improves local operating efficiency**